

HYUNDAI HHD21-TL7060X

A+++

A++ A+

Λ

_

C

D

D

kWh/annum









65 dB

Product data sheet for household cooker hoods according to regulation (EU) No. 65/2014					
Brand	HYUNDAI				
Model	HHD21-TL7060X				
Annual Energy Consumption (AEC _{hood})		kWh/a	94		
Energy Efficiency Class			D		
Fluid Dynamic Efficiency (FDE _{hood})			6,5		
Fluid Dynamic Efficiency Class			F		
Lighting Efficiency (LE _{hood})		lux/W	13		
Lighting Efficiency Class			D		
Grease Filtering Efficiency (GFE)		%	70		
Grease Filtering Efficiency Class			D		
Air Flow at minumum speed in normal use		m³/h	165		
Air Flow at maximum speed in normal use		m³/h	300		
Air Flow in use intensive or boost setting		m³/h	-		
Acustic Power emission in normal use at minimum speed		dB	57		
Acustic Power emission in normal use at maximum speed		dB	65		
Acustic Power emission in boost mode		dB	-		
Power Consumption in off mode (Po)		w	0		
Power Consumption in standby mode (Ps)		w	-		
Integration Directive	EU 66/2014				
Time Increase Factor (f)			1,8		
Energy Efficiency (EEI _{hood})			98,7		
Airflow at best efficiency point (Q _{BEP})		m³/h	193		
Pressure at best efficiency point (P _{BEP})		Pa	171		
Electric power input at the best efficiency point (W_{BEP})		w	140		
Electric power input for lighting system (W_L)		w	5		
Avarage illuminance on the cooking surface (E _{middle})		lux	65		

Brand	HYUNDA	AI	
Model	HHD21-TI	21-TL7060X	
Annual Energy Consumption (AEC _{hood})		kWh/a	94
Energy Efficiency Class			D
Fluid Dynamic Efficiency (FDE _{hood})			6,5
Fluid Dynamic Efficiency Class			F
ighting Efficiency (LE _{hood})		lux/W	13
ighting Efficiency Class		23	D
Grease Filtering Efficiency (GFE)		%	70
Grease Filtering Efficiency Class			D
Air Flow at minumum speed in normal use		m³/h	165
Air Flow at maximum speed in normal use		m³/h	300
Air Flow in use intensive or boost setting		m³/h	-
Acustic Power emission in normal use at minimum speed		dB	57
Acustic Power emission in normal use at maximum speed		dB	65
Acustic Power emission in boost mode		dB	-
Power Consumption in off mode (Po)		w	0
Power Consumption in standby mode (Ps)		w	-
Integration Directive	EU 66/2014		
Time Increase Factor (f)			1,8
Energy Efficiency (EEI _{hood})			98,7
Airflow at best efficiency point (Q _{BEP})		m³/h	193
Pressure at best efficiency point (P _{BEP})		Pa	171
Electric power input at the best efficiency point (W_{BEP})		w	140
Electric power input for lighting system (W _L)		w	5
Avarage illuminance on the cooking surface (E _{middle})		lux	65